

What is claimed is:

1           1.     A method for channel decoding and error correcting modulated  
2 data reproduced from an optical disc comprises the steps of:

3           (a) setting a channel code including channel data patterns of channel data  
4 symbols and information data symbols which correspond to respective channel  
5 data patterns;

6           (b) producing demodulated data including the information data symbols  
7 and erasure flags by demodulating the channel data symbols, using the channel  
8 code; and

9           (c) performing error-erasure correction on the information data symbols  
10 produced in the step (b), using error locations indicated by the erasure flags  
11 having a predetermined value,

12           wherein the step (b) of producing demodulated data comprises the steps  
13 of;

14           (b1) outputting the information data symbols if the channel code has the  
15 information data symbols corresponding to the channel data patterns; and

16           (b2) outputting erasure symbols as the information data symbols and  
17 setting the erasure flags to the predetermined value if the channel code has no  
18 information data symbols corresponding to the channel data patterns.

1           2.     The method of claim 1, wherein each the erasure symbols is one of  
2 the information data symbols in the channel code or a predetermined value.

1           3.     The method of claim 1, wherein the channel code is one of an EFM  
2     code and an EFM+ code.

1           4.     The method of claim 3, wherein the demodulated data includes 8-  
2     bit information data symbols and 1-bit erasure flags.

1           5.     A system for channel decoding and error correcting modulated data  
2     reproduced from an optical disc comprises:

3           a channel decoder, including a channel code having channel data  
4     patterns that channel data symbols can have and information data symbols  
5     which correspond individually to the channel data patterns, and for producing  
6     demodulated data having the information data symbols and erasure flags by  
7     demodulating the channel data symbols, using the channel code.

8           a memory for storing the demodulated data outputted from the channel  
9     decoder; and

10          a decoding unit for performing an error-erasure correction on the  
11     information data symbols, using error locations indicated by the erasure flags  
12     having a predetermined value,

13          wherein the channel decoder outputs the information data symbols if the  
14     channel code has the information data symbols corresponding to the channel  
15     data patterns, and the channel decoder outputs erasure symbols as the  
16     information symbols and sets the erasure flags to the predetermined value if the

17 channel code has no information data symbols corresponding to the channel  
18 data patterns.

1 6. The system of claim 5, wherein each of the erasure symbols is one  
2 of the information data symbols in the channel code or a predetermined value.

1 7. The system of claim 5, wherein the channel code is one of an EFM  
2 code and an EFM+ code.

1 8. The system of claim 7, wherein the demodulated data includes 8-  
2 bit information data symbols and the 1-bit erasure flags.

1 9. The system of claim 5, wherein the decoding unit includes:  
2 a means for receiving from the memory code words obtained from the  
3 demodulated data;  
4 a means for detecting a code word having errors more than a  
5 predetermined number; and  
6 a means for providing second erasure flags of a predetermined value to  
7 information data symbols of the detected code word.

1 10. The system of claim 9, wherein the predetermined number is two  
2 (2) for a compact disc (CD) system or five (5) for a digital versatile disc (DVD)  
3 system.

11. The system of claim 9, further including:  
a means for deinterleaving data from the decoding unit to generate  
deinterleaved code words containing the information data symbols and the  
second erasure flags; and  
a second decoding unit for performing error-erasure correction on the  
information data symbols of the deinterleaved code words using the second  
erasure flags.

12. A method for correcting errors and erasures in modulated channel  
data reproduced from an optical disc, comprising the steps of:  
providing a channel code having channel data patterns of the modulated  
channel data and information data symbols corresponding to the channel data  
patterns, respectively;  
comparing channel data symbols of the modulated channel data with the  
channel data patterns in the channel code;  
producing information data symbols corresponding to channel data  
patterns of the channel data symbols to form demodulated data;  
producing erasure symbols with erasure flags to form the demodulated  
data when the channel code has no channel data patterns matching the channel  
data symbols;  
providing code words obtained from the demodulated data; and  
correcting errors and erasures in the code words using the erasure flags.

1            13.    The method of claim 12, wherein the channel code is an EFM code  
2    for a compact disc (CD) system and an EFM+ code for a digital versatile disc  
3    (DVD) system.

1            14.    The method of claim 12, further including the steps of:  
2            detecting a code word having errors more than a predetermined number;  
3    and  
4            providing second erasure flags of a predetermined value to the detected  
5    code word.

1            15.    The method of claim 14, wherein the second erasure flags are  
2    provided to the detected code word such that each of the second erasure flags is  
3    attached to each of information data symbols or erasure symbols of the detected  
4    code word.

1            16.    The method of claim 14, further including the steps of:  
2            deinterleaving the code words on which the correcting step has been  
3    performed; and  
4            correcting errors and erasures in the deinterleaved code words by locating  
5    defective symbols using the second erasure flags.